



STEAM GENERATOR

STEAM BOX VAC PRO

Body material

Stainless steel AISI 304 (BA)

Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume

7,3 L

Tanks

Water: 14 L | Det: 14 L

Maximum output

4,8 - 8,4 - 11,1 - 15,6 kW

Boiler output

3,6 - 7,2 - 10 - 14,4 kW

Steam production

97 - 194 - 272 - 388 g/min

5,9 - 11,6 - 16,3 - 23 Kg/h

Power supply

3~ 400V - 50/60 Hz

Steam T°

183° C

Detergent T°

90° C - 160° C

Vacuum output

1 kW

Vacuum drum capacity

7,5 L

Air flow

200 m3/h

Depression

2200 mm

Power cord

8 m

Weight


82 Kg

Packaging

115x65x125 cm



induction turbine



APPLICATIONS



Three-phase steam generator for usage in the industrial sector, with a stainless-steel body (watertight protection IPX5), **unlimited steam autonomy** thanks to the automatic refilling system with either an internal water tank (electromechanical water level control system inside the boiler – True Temp™) or directly with a water mains connection. **Possibility to inject detergent or hot water together with steam**. **Equipped with an integrated wet&dry vacuum cleaner with an induction turbine**. The steam generator's front panel is **equipped with an electric console with commands for a timer, a thermometer and a pressure gauge**; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



TOOLS



GEYSER I 10 BAR
Steam 183°C



RADAMES 10 BAR
Steam & vacuum 183°C

